

X4080I-U1 / X4080I-U1x2

40" Multi-Touch Display



The X4080I-U1 is a 40"HD LCD display with LED backlighting technology. Its slim design makes it attractive in a number of verticals, including retail and hospitality. The design is further enhanced by an Open Pluggable Specification (OPS) slot and multiple connectivity options. It is integrated with infra red, a multi-touch technology, and is offered as a dual-touch (X4080I-U1x2) or multi-touch (X4080I-U1) solution. The multi-touch solution features six touch points and is Windows 8 ready.

AT A GLANCE


- HD LCD display
- Slim Bezel
- LED backlighting
- Energy efficient
- OPS slot

APPLICATIONS

- Retail
- Hospitality
- Factory
- Education

Specifications

Panel	X401S
Viewable Image Size	40"
Touch Technology	Infrared
Pixel Pitch	0.46 mm
Brightness	500cd/m ²
Contrast Ratio	3500:1
Aspect Ratio	16:9
Resolution	1920 x 1080
Viewing Angle	178° Vertical; 178° Horizontal
Synchronization	H: 31.5 - 91.1 kHz; V: 50 - 80 Hz
Connectivity	VGA 15-pin D-sub, BNC Composite, Audio Mini-Jack, DisplayPort Audio, HDMI Audio
Compatibility	PC and Mac
Power Consumption	On: 110W; Standby: <1W
Dimensions (WxHxD)	37.05 x 21.962 x 2.52 in (without stand) - IR
Weight	54 lbs (without stand)
VESA Hole Configuration	300 x 300mm (4-hole)
Operating Temperature	41 - 104° F / 5 - 40° C
Operating Humidity	20 - 80%
Standards	FCC Class B, C-UL
Limited Warranty	3 Years Parts and Labor, including Backlight



220 Tradesmen Dr.
Hutto, Texas 78634
800.320.5944
sales@touchsystems.com